

Elegant & corrosion resistant:
Swing-Door for strong conditions of use.

Exterior/Interior Door

Aluminium-Swing-Door ELA Steel-Swing-Door LFS and MFS



Transparency for inside and outside.

The Swing-Door available in steel or aluminium is a manually operated door for inside and outside areas.

Automatic closing.

The integrated shapely spring mechanism closes the door automatically.

Without any effort.

Transparency is safety.

The translucent tear resistant curtain makes transport routes safe due to the unobstructed view on both sides and it provides very good light conditions in working areas.

Freezing certainly too.

A special PVC type allows installation in freezer areas up to minus 40 degrees Celsius.

Aluminium model, type ELA

Size

Width (CW) max.	2500 mm
Height (CH) max.	2500 mm
Optional: low profile frame	80x8 mm

Medium industrial model, type LFS

Size

Width (CW) max.	3000 mm
Height (CH) max.	3000 mm
Optional: low profile frame	80x8 mm

Heavy industrial model, type MFS

Size

Width (CW) max.	4200 mm
Height (CH) max.	4200 mm
Low profile frame	80x8 mm

Door leaf:

PVC app. 7 mm translucent with enforced corners

Optional:

PVC app. 10 mm translucent with enforced corners

PVC with coloured fabric lining and clear view stripe

PVC with coloured fabric lining and window

PVC-impact protection or fabric lining for strengthening arranged to customers specifications

PVC app. 7 mm translucent for freezer areas up to -40 °C

Operation:

Manually, adjustable spring closer integrated in door profile

Opening angle 90°

Supplementary equipment:

Magnetic door holder hinge with angle bracket

Touch automation

Pneumatic rotary drive