

Fast, quiet and for areas with strong draft.

Transspeed BS



Compact and stable construction.
The High-Speed-Rolling Door Transspeed with permanent curtain tension.

For easy maintenance the complete door construction is accommodated in the selfsupporting side construction. The drive linked with frequency converter accelerates up to 1.8 meters per second. For your safety an anodised profile with integrated safety strip is installed at the bottom of the door.



Optional mosquito curtain protection, as complete curtain or partly available

Door size

Width (CW) max. 5000 mm
Height (CH) max. 5000 mm

Control system

Microprocessor control system TS 971 with CEE-connector

Speed

Drive is linked with frequency converter
Opening speed max. 1,8 m/s
Closing speed max. 0,8 m/s






Emergency opening

Manual crank
Optional: Emergency chain

Curtain

PVC-coated fabric with window and permanent curtain tension.
Steel wind-pressure bars with double cam rollers on the side.

Curtain colours

RAL 1018	Zinc yellow	
RAL 2004	Pure orange	
RAL 3002	Carmine red	
RAL 5010	Gentian blue	
RAL 7038	Agate grey	

Optional

PVC translucent with vertical fabric strips.
PVC approx. 3 mm 2 fabric inlets, window and steel wind-pressure bars for wind class 3

Wind class resistance (EN 12424)

Class 2