

The reasonable priced horizontal High-Speed Rolling Door:  
Fast opening speed, compact technology.

# Transsprint S



Transsprint-S also opens with an opening speed of app. 3 meters per second. Both types need a very low lintel height due to their construction.

### Safe and compact

On power loss the door opens automatically up to a width of 2 meters. The safety bars are integrated in sturdy bars and stop door movement immediately in case of danger.

### There's more to it

When built in stainless steel the Transsprint-C and Transsprint-S meets all hygienic requirements of the food processing industry, the chemical industry and the pharmaceutical industry.

Transsprint S in stainless steel approved for the food industry.



### Door size

Width (CW) max.	4000 mm
Height (CH) max.	4000 mm

### Control system

Microprocessor control system TS 971 with CEE-connector

### Speed

Drive is linked with frequency converter	
Opening speed max.	3,0 m/s
Closing speed max.	1,0 m/s






### Emergency opening

Automatically opening approx. 2 m after power loss.

### Curtain

PVC-coated fabric with big window

### Curtain colours

RAL 1018	Zinc yellow	
RAL 2004	Pure orange	
RAL 3002	Carmin red	
RAL 5010	Gentian blue	
RAL 7038	Agate grey	

### Wind class resistance (EN 12424)

Class 1